



# Remote Area Lighting System



Hsecurity continues to lead the industry: The new Spot Beam and Infrared Beam models save lives and defeats enemy threats.

With a tight, 10° beam, the new HS-LER-124-2000B (Spot Light) reaches hundreds of yards for effective search and rescue, law enforcement and military operations. And with a run time of up to 15 hrs, the HS-LER-124-2000B will outlast the longest night of the year.

The HS-LER-124-2000B (Infrared) enhances Night Vision optics to provide improved visibility in complete darkness. With a low thermal signature, is perfect for covert surveillance.

Code **HS-LER-124-2000B**

## Technical Specifications

### Applications



#### Light Source

LED Type	LED Life	Tested Lumen Value
High Flux LED	50000 hrs.	1000 (Low) 2000 (High)
Lamp Heads	Number of LEDs	Beam Spread
1	24 LEDs per head	10°
Brightness Settings		
2		

#### Power Source

Battery Type	Battery Burn Time	Battery Charging Time
12v Rechargeable, Sealed	15 hrs. (Low) 8 hrs. (High)	5 hrs. from full discharge
Battery Life	Low Battery Warning	12V Primary Sockets
500 cycles	Intermittent Blinking	1
12V Auxiliary Sockets	Watts	Voltage
1	24	12



# Remote Area Lighting System



## Technical Specifications

### Dimensions & Weight

Head Length	Head Width	Head Depth
6.5" (16.5 cm)	7.87" (20 cm)	2.56" (6.5 cm)
Width Closed	Length Closed	Height Closed
7.87" (20 cm)	15.75" (40 cm)	9.06" (23 cm)
Mast Height Extended	Cord Length (Retracted)	Weight
32.28" (82 cm)	13.78" (35 cm)	22.05 lbs. (10 kg)

Approvals	CE	Approved
	CE Certificate	Yes
	RoHS (Restriction of Hazardous Substances) Compliant	Approved


Code **HS-LER-124-2000B**

## Orden Information

Product Code	N° Focus	N° Led
HS-LER-124-2000B	1	24

Color  Black

## Accesorios

Code	Description	Image	Code	Description	Image
HS-LER-124-2000CJ	Case		HS-LER-124-2000CR	Spare LED Head	
HS-LER-46-12000TP	Tripod		HS-LER-26-12000CV1	12/24V Vehicle Charger CV1	
HS-LER-124-2000TBP	Tear-Off Back Pack		HS-LER-46-12000CE1	Gen I Extension Cord (Blue Connector) 118 inches (3m)	
HS-LER-124-2000BP	Back Pack		HS-LER-124-2000CU	RALS Universal Charger	