



Remote Area Lighting System



- New improved version - Generation 3
- Up to 15 hours of burntime
- 3000 lumens of brightness
- Maintenance Free LED Array with life expectancy of 50,000 hours
- Fully extendable mast with 360 degree rotating head
- Low Battery Warning System
- Waterproof Rubber Activation Switch
- Mast Extension Lock

Code **HS-LER-16-3000A**

Technical Specifications

Applications



Light Source

LED Type	LED Life	Tested Lumen Value
High Flux LED	50000 hrs.	1500 (Low) 3000 (High)
Lamp Heads	Number of LEDs	Beam Spread
1	6 LEDs per head	125°
Brightness Settings		
2		

Power Source

Battery Type	Battery Burn Time	Battery Charging Time
12v Rechargeable, Sealed	15 hrs. (Low) 8 hrs. (High)	5 hrs. from full discharge
Battery Life	Low Battery Warning	12V Primary Sockets
500 cycles	Intermittent Blinking	1
12V Auxiliary Sockets	Watts	Voltage
1		12



Remote Area Lighting System



Dimensions & Weight

Head Length	Head Width	Head Depth
6.5" (16.5 cm)	7.87" (20 cm)	2.56" (6.5 cm)
Width Closed	Length Closed	Height Closed
7.87" (20 cm)	15.75" (40 cm)	9.06" (23 cm)
Mast Height Extended	Cord Length (Retracted)	Weight
32.28" (82 cm)	13.78" (35 cm)	22.65 lbs. (10.27 kg)

Approvals	CE	Approved
	CE Certificate	Yes
	RoHS (Restriction of Hazardous Substances) Compliant	Approved

Code **HS-LER-16-3000A**

Orden Information

Product Code	N° Focus	N° Led
HS-LER-16-3000A	1	6

Color  
 Yellow Black

Accessories

Code	Description	Image	Code	Description	Image
HS-LER-124-2000CJ	Case		HS-LER-26-12000CV1	12/24V Vehicle Charger CV1	
HS-LER-46-12000TP	Tripod		HS-LER-26-12000CV2	12/24V Vehicle Charger CV2	
HS-LER-124-2000TBP	Tear-Off Back Pack		HS-LER-46-12000CE1	Gen I Extension Cord (Blue Connector) 118 inches (3m)	
HS-LER-124-2000BP	Back Pack		HS-LER-16-3000RC	Extension Cord (Red Connector) 118 inches (3m)	
HS-LER-16-3000SA	Socket Adaptador		HS-LER-16-3000UC	Universal Charger	
HS-LER-124-2000CR	Spare LED Head				